



Products for the Professional

UNICLASS	EPIC
CI/SfB	

November 2008

Product Data Sheet

Acoustic Matting

Description:

Nicobond Acoustic Matting – Designed as part of a sound reduction system to comply with Building Regulations 2000 Document E. Manufactured from a fine granulate of recycled rubber with cork and PU elastomeric bonding agent, supplied in blue granulate and beige cork having a fine granulate structured surface. Flexible sheet underlay with good lay-flat properties. Allows installation of underfoot comfort, acoustic and thermal insulation on poorly insulated surfaces. Makes flooring flexible and warm underfoot. In staircase areas, prevents transfer of sound and premature floor covering wear from impact.

Substrate Preparation:

The substrate must be level, sound, and free from cracks, dry, clean and free from materials that would impair adhesion. Test the substrate in accordance with applicable standards. If Required thoroughly vacuum the surface, then prime and apply Nicobond smoothing compound, according to substrate type and occupational use.

Application

Apply a layer of general purpose vinyl adhesive to the concrete base, following the manufacturer's instructions. Lay the Nicobond Acoustic Mat and smooth out with a light roller to remove any air bubbles. Cover joints between mats with crack tape to prevent tile adhesive penetrating to the base which could cause a sound bridge. Once the floor adhesive is dry, insert the polyethylene backing rod around the perimeter at wall/floor junctions to isolate the floor. Apply the tile adhesive following recommended procedures. Ensure final perimeter joints are filled with a suitable mastic sealant.

Features

- Easy to cut and install
- Remains continually elastic
- Can be used under Tiles, Stone, Vinyl, Wood, Carpet etc.
- Document E compliant
- Minimum Build height with permanent resilience
- Good acoustic and thermal properties
- Medium duty rating for coefficient of restitution
- Compatible with undertile heating systems.
- Fully recycled material

Dimensions/Tolerances	
Length:	Supplied in 10mt rolls x 1000mm wide +/- 1.5% (DIN 7715 Part 2 Class M4)
Available Thickness:	5mm
Density:	Approx 390 kg/m ²
Physical Properties	
Tensile Strength:	Approx 0.6 N/mm ²
Elongation at break:	5mm approx 60%
Compressive Modulus At 40% strain: (DIN 53571)	Min 1.2 MPa
Coefficient of friction (dry)	Average 0.66 (GS-V-28)
Service Temperature Range	-30°C to +80°C
Environmental behaviour:	Limited resistance to acid and alkali solution.
Final Performance: 11mm glazed tile covering ISO 140-8: 1998	
Thickness	5mm
DLW	20dB
Flammability Rating	B2

Protection of the Workplace and the Environment:

No special no special measures are required.

Disposal:

All product residues are treated as normal construction waste.



N & C Building Products Limited
 41-51 Freshwater Road
 Chadwell Heath
 Romford
 Essex RM8 1SP
 Tel: 020 8586 4600
 Fax: 020 8586 4646
 Email: info@nichollsandclarke.com
 Web: www.ncdirect.co.uk