

# Nicobond Wet Room Waterproofing Accessories

### Nicobond Wet Room Waterproof Tanking Sheet

Used in conjunction with Nicobond Plastic Ply the Nicobond Wet room Tanking Sheet is designed to cover surfaces subject to movement such as chipboard, plywood and timber floor boards. Made from UV resistant polyethylene and faced with glass fibre fleece Nicobond Wet Room Tanking Sheet offers superb protection against moisture penetration, has high flexibility and is part of a total solution for a watertight barrier.

### Application

The Tanking sheet is to be firmly bedded down onto the Nicobond PlasticPly using a thin layer of Nicobond Rapidflex Adhesive. Cover joints between adjacent sheets with the Waterproof Tape.

### Nicobond Wet Room Waterproof Tape

A key component in the Nicobond Wet room system. A strong polyethylene material backed with a self adhesive butyl rubber layer, the tape is used for bridging and reinforcing internal corners and floor and wall joints. Simply remove the backing release paper and press the tape firmly into position.

### Nicobond Wet Room Waterproof Internal and External Corners

To ensure complete waterproofing in internal and external corners use the special pre-formed angled corners. Simply remove the backing release paper and press the tape firmly into position

### Nicobond Wet Room Waterproof Pipe Collars

For efficient sealing around pipework, valves and drainage outlets. Available as a small or large collar with pre cut holes. Simply remove the backing release paper and press the tape firmly into position



### Application Data

<b>Colour: Tanking Sheet:</b> <b>Tape:</b> <b>Corners:</b> <b>Pipe Collars</b>	Red Grey – Self Adhesive Grey – Self Adhesive Grey – Self Adhesive
<b>Pack Size:</b> <b>Tanking Sheet:</b> <b>Tape:</b> <b>Corners:</b> <b>Small Pipe Collar:</b> <b>Large Pipe Collar:</b>	10mtrs x 750mm wide 20mtrs x 80mm wide 120*120mm 100*100mm Precut hole 11mm diameter 375*375mm Precut hole 39mm diameter
<b>Operating Temperature</b>	5°C - 70°C

### Features

- Part of the Nicobond Total Wet Room Solution System
- New self adhesive backing for speedy installation
- All accessories highly flexible
- Good crack bridging properties
- Low water vapour permeability

### Application for walls and concrete/screeded floors.

Apply the first coat of membrane to the walls and wall/floor junctions and then place the internal corners into position with a firm action. Then apply membrane to the rest of the floor area. Once the first coat has dried apply a second coat of membrane building up to a minimum thickness of 0.6mm.

### Specification

The Accessories shall be Nicobond Wet Room Waterproofing Accessories as manufactured by N&C Building Products Limited, 41-51 Freshwater Road, Chadwell Heath, Romford, Essex, RM8 1SP, England. Tel: 020 8586 4600 and shall be applied strictly in accordance with the Manufacturer's current data sheets and instructions.

N & C Building Products Limited  
41-51 Freshwater Road  
Chadwell Heath  
Romford  
Essex RM8 1SP

Tel: 020 8586 4600  
Fax: 020 8586 4646

Email: info@nichollsandclarke.com  
Web: www.nichollsandclarke.com

