

Product Data Sheet

# Temporary Protection Sealer

**Description:**

A water based temporary protective sealer for tiles prior to grouting, which protects the surface against discolouration from pigmented grouts. Suitable for use on most surfaces including marble, ceramics, mosaics, natural stone, terracotta, etc. Used undiluted and applied in two coats prior to grouting.

**Features:**

Water-based polymer emulsion  
 Walls and floors  
 Suitable for most surfaces  
 Protects surface  
 Easy to wash off

**Application:**

**IMPORTANT: Ensure tile surfaces are clean, dry and free from contamination. Do NOT use in temperatures below 5°C or in damp conditions. Do NOT dilute. Use before grouting begins .**

1. Apply onto the area to be treated with clean, colour-fast lint free cloth. Ensure complete coverage, but avoid application to un-grouted joints.
2. Allow the first coat to dry.
3. Apply a second coat and allow to dry.
4. Apply grout as instructed.
5. On completion of grouting and after grout has set, Remove the sealer by washing the surface with clean water.



**Application Data**

Unit size	2.5 litres
Mixing ratio	Not required
Consistency of mix	Liquid
Packaging	2.5 litre jerry can

**Coverage**

(2 coat application) 10-15 m<sup>2</sup>/Litre depending on surface porosity  
 2.5Litre Pack would cover 25-37m<sup>2</sup> for a 2 coat application.

**Tools required**

Colour fast lint free cloth

**Shelf life**

2 years

**Storage**

Store in a cool dry place away from frost and direct sunlight.  
 Store between 5°C and 30°C. **Keep out of reach of children and animals**

**Health & Safety Advice**

Contact with eyes and skin should be avoided.  
 IF ON SKIN: Wash with plenty of soap and water.  
 IF IN EYES: Rinse thoroughly with water.  
 If medical advice is needed, have product container or label at hand. Do not use for medical or hygiene purposes. Do not mix with any other preparations. Do not ingest. If product is ingested, then seek medical advice. Always test on an inconspicuous area prior to use and only proceed when satisfied with the results. Rinse hands after use.  
**KEEP OUT OF REACH OF CHILDREN AND ANIMALS.**  
 Read Label before use



The Temporary Protection Sealer shall be Nicobond Temporary Protection Sealer as manufactured by N&C Building Products Limited, 41-51 Freshwater Road, Chadwell Heath, Romford, Essex, RM8 1SP, England. Tel: 020 8586 4600 and shall be applied strictly in accordance with the Manufacturer's current data sheets and instructions.

Email: [info@nichollsandclarke.com](mailto:info@nichollsandclarke.com)  
 Web: [www.nichollsandclarke.com](http://www.nichollsandclarke.com)