

Product Data Sheet

Screened Super Cleaning Crystals

Description

A white granular, crystalline, medium alkalinity detergent containing a high proportion of special surfactants. For removing dirt, fats, grease, oils, polish from all types of sub-floors, including things that would be attacked by solvent-based cleaners, prior to the application of Nicobond Screened products.

Preparation

Scrape off the floor any thick layers of grease, fats, plaster, paint and all loose material.

Mixing

Lightly contaminated floors, add about 1/2 kg Nicobond Screened Super Cleaning Crystals to 5 litres of hot, not boiling, water in a plastic or rubber bucket (not aluminium nor galvanised). **Heavily contaminated floors**, as above but increase quantity of Nicobond Screened Super Cleaning Crystals to about 1kg per 5 litres of hot water.

Application

Lightly contaminated floors, vigorously brush hot solution onto the floor at rate of approx. 5 litres solution to 10m² depending on condition of surface. Allow solution to stay on floor for at least 15 - 30 minutes. **Heavily contaminated floors**, Treat as above using prepared solution.

Method of Treatment

Wash away reacted solution, dirt etc. from floor with broom and jet of water from hose pipe. Rinse floor with fresh water until it is clean. Repeat the application of mixed solutions if necessary until floor is thoroughly clean. Brush off surplus water and allow floor to dry before any subsequent floor treatment is carried out. Nicobond Screens may be applied to damp floors.

Coverage

A 10m² kit contains sufficient material to apply one thin even coat to a maximum area of 20m² on a good surface. This coverage will be considerably reduced on rough or porous surfaces.

Cleaning

Mixing tools and squeegees should be cleaned with white spirit before the Nicobond Screened Pitch Epoxy DPM has set.

Important Notes about membranes: Solvent based cleaners should not be used since residual solvent in the subfloor may affect the membrane. Nicobond Screened Pitch Epoxy DPM must not be applied to anhydrite, magnesite or similar composition screeds, nor any surfaces regarded as suspect. Not proof against hydrostatic pressure.

Application Data	
size :	8kg
Coverage	1kg of Nicobond Screened Super Cleaning Crystals in 10 litres of water will cover approx. 20m ² depending on floor surface.
Application time	15 to 30 Minutes Dependant on condition of surface.
Mix Ratio (light contamination)	1/2 kg Nicobond Screened Super Cleaning Crystals to 5 litres of hot, not boiling, water
Mix ratio (heavy contamination)	1kg Nicobond Screened Super Cleaning Crystals per 5 litres of hot water.
Installation Temperature	Minimum 5°C
Storage	Store in a cool, dry place. Opened containers should be resealed after use. Shelf life up to 12 months.

Features

For removing dirt, fats, grease, oils, polish from all types of sub-floors
 Readily soluble in water
 Does not contain caustic soda
 Safe for use on asphalt
 High detergent content.

Precautions Health & Safety Advice

Nicobond Super Cleaning Crystals are an alkaline detergent and classified as a Corrosive and can cause burns. Avoid contact with skin and eyes. Do not breathe dust. Wear suitable protective clothing, chemical resistant gloves and eye/face protection. Keep away from children.

The relevant Material Safety Data Sheet can be obtained from www.nichollsandclarke.com or directly from N & C Building Products Ltd at the address below.



N & C Building Products Limited
 41-51 Freshwater Road
 Chadwell Heath
 Romford
 Essex RM8 1SP
 Tel: 020 8586 4600
 Fax: 020 8586 4646

Email: info@nichollsandclarke.com
 Web: www.nichollsandclarke.com