

## ALKALI RESISTING PRIMER

**Dulux Trade** Alkali Resisting Primer is a solvent-based primer particularly suitable for use on interior and exterior masonry surfaces, including plaster, that may contain alkalis. It is also highly recommended for its outstanding stain-sealing properties, and will help seal fire damaged surfaces after very thorough cleaning and rinsing. Can also be used to prime surfaces treated with fire retardant chemicals.

### KEY BENEFITS

- Plaster & Masonry Surfaces
- Seals Fresh, Alkaline Surfaces
- Blocks Stains such as Nicotine & Fire Damage

### PRODUCT INFORMATION

#### Typical Use

Interior and exterior masonry surfaces that may contain alkalis.

#### Pack Size

1L and 5L.

#### Colour Range

Off-white.

#### Composition (nominal)

**Pigment:** Titanium Dioxide, Zinc Oxide and Alkali Resisting Extenders.

**Binder:** Oleoresin.

**Solvent:** White Spirit.

#### Volume Solids

48% (nominal).

### SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as efflorescence, dirt, grease or wax. Where necessary, surfaces should be rubbed down using a suitable abrasive paper and then dusted off (refer to your COSHH Assessment). Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

### SYSTEMS INFORMATION

**STIR THOROUGHLY BEFORE USE.** After suitable surface preparation, apply 1 coat of **Dulux Trade** Alkali Resisting Primer to bare or stained surfaces. Finish with an appropriate **Dulux Trade** paint system.

### APPLICATION METHOD

Brush only.

As with all solvent based paints (according to British Standard BS 6150), do not use in temperatures below 5°C.

#### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 9m<sup>2</sup> per litre.

#### Spray Recommendations

For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.

#### Drying Times

*Single coat at standard thickness:*

**Touch Dry:** 8-12 hours.

**Recoat:** 16-24 hours.

#### Cleaning Up

After use, remove as much paint as possible from brushes before cleaning with brush cleaner.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/lpp](http://duluxtrade.co.uk/lpp).



# ALKALI RESISTING PRIMER

## Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

## VOC

EU limit value for this product (cat : A/g): 350g/l (2010). This product contains max. 350g/l VOC. VOC Content: High (25-50%).

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

***Always read full Health, Safety & Environmental Information on can before use.***

Safety datasheet (SDS 301) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre, or visiting [duluxtrade.co.uk](http://duluxtrade.co.uk).

AkzoNobel, the AkzoNobel logo, the Fluorish logo, Dulux Trade, the Planet Possible logo and Community RePaint are all trademarks of the AkzoNobel group. © AkzoNobel 2014.



At **Dulux Trade**, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp)