



UNICLASS L6412:P21	CAW M10
CI/SfB	(43) Yq2

Technical data sheet

January 2015

Heavy Duty Spray

A versatile heavy duty aerosol spray adhesive for fast track applications, bonds a wide variety of materials and economical to use.



Features

- Rapid bond formation
- Economical to use
- CFC free
- Easi - flo variable valve
- Strong bond
- Bonds a wide variety of materials
- 500ml

The adhesive shall be Heavy Duty Spray as manufactured by N&C Building Products Limited, 41-51 Freshwater Road, Chadwell Heath, Romford, Essex, RM8 1SP, England. Tel: 020 8586 4600 and shall be applied strictly in accordance with the manufacturer's current data sheets and instructions.





Product Description

Heavy Duty Spray gives a rapid bond formation and with its foaming formula for low soak in, it is ideal to use on a variety of materials including wood, concrete, stone, tiles, rubber, foam, metals, rigid plastics, polyethylene, canvas fabrics, cardboard, paper and cork.

It is also ideal for fixing polyethylene sheeting for enclosures prior to asbestos removal, for fixing thermal insulation and for packaging applications such as palletising or case sealing.

It may be used for foam bonding, upholstery, automotive, carpets, trim and is useful for bonding instead of double sided tape.

It is not suitable for use with plasticised PVC or expanded polystyrene.

Application

Always shake well before use. Surfaces should be clean, dry and free from grease.

Spray adhesive from approximately 15 – 20cm onto one or both surfaces.

For one-way application, let adhesive dry for 30 seconds until tacky, then press into position.

For two-way application, spray both surfaces and allow to dry for 2-5 minutes before bonding.

For temporary bonding, spray one surface and allow to dry for 2-5 minutes before bonding.

To prevent the spray nozzle from blocking, at the end of each period of use, turn the can upside down and press the nozzle until spray is clear of adhesive.

Technical Information

Specification	Heavy Duty Spray
Type	Aerosol Adhesive
Appearance	Straw
Type	Synthetic Rubber/Resin
Application	Aerosol Spray
Application Temp:	+5° C to +40° C
Drying Time	2-5 minutes
Packaging	500ml

Cleaning

Heavy Duty Spray can be removed with most solvent cleaners.

Shelf Life

12 months unopened from the date of packing.

Storage

This product must be stored clear of the ground, under dry conditions, out of direct sunlight between 5° C and 25° C. Protect from frost. If allowed to freeze N&C Building Products cannot guarantee the performance of the product.

Health & Safety Advice

Heavy Duty Spray is classified under the Chemicals (Hazard Information and Packaging for Supply) Regulations.

The relevant Material Safety Data Sheet can be obtained from the website or directly from N&C Building Products Ltd at the address below.

N & C Building Products Limited
41-51 Freshwater Road
Chadwell Heath
Romford
Essex RM8 1SP
Tel: 020 8586 4600
Fax: 020 8586 4646
Email: info@nichollsandclarke.com
Web: www.ncnicobond.com

