



Products for the Professional

UNICLASS	EPIC
Cl/SfB	(4-) Yq

Product Data Sheet

September 2020

Special fx

Description

A range of special additives which when combined with Nicobond Starlike evo Extreme Performance Grout and Nicobond Super Grout Pro bring a unique and attractive sparkle, metallic or luminescent effect to the grout.

Uses

When using with Nicobond Starlike evo Grout all three glitter options may be used. 1 x 75gm sachet per 2.5kg tub

To produce Starlike Metallic colours use Starlike evo 113 Neutral with the appropriate metallic additive. 1 x 100gm sachet per 2.5kg tub of 113 Neutral.

To produce Starlike Night Vision select one of the appropriate Starlike evo colours and use the Night Vision additive. 1 x 200gm sachet per 2.5kg tub. Refer to Starlike evo data sheet or wallet for colour options.

When used with Nicobond Super Grout Pro only Silver and Gold may be selected. 2 x 75gm sachets per 5kg tub.

Note: Starlike evo Glitter Galaxy is a very fine material and would make the Super Grout Pro very stiff to work with.

Note: Starlike Special fx are not suitable for use with cement based grouts or other products not specified in this data sheet.

Features

- Add Galaxy to produce a shimmering finish**
- Add Silver to create a silver glitter effect**
- Add Gold to create a gold glitter effect**
- Add Night Vision for a stunning luminescent effect**

- Great appeal to designers
- Enhances plain tiles
- Easy to apply
- For internal and external applications
- Suitable for walls and floors



Application Data

Colour	Silver/Galaxy/Gold/Metallic/ Night Vision
Mixing: Starlike evo Grout	Mix entire contents of the sachet with the 2.5kg tub of mixed Starlike evo Grout
Mixing: Super Grout Pro	Mix entire contents of up to two sachets with the 5kg tub of ready mixed Super Grout Pro.
Glitter	Polyester/Metal/Epoxy
Ready for service	Full cure after 5 days at 23°C
Installation Temperature	12°C - 30 °C
Serviceable Temperature	-20°C to + 100°C
Packaging	75gm/100gm/200gm sachets see Uses.

Surface Preparation

Joints to be filled should be clean and free from grease, dust and any contamination which may prevent adhesion.

Mixing

Mix the entire contents of the sachet/sachets of additive with the selected grout until a uniform distribution of additive has been achieved.

Tile Fixing

Tile fixing should be carried out in accordance with BS 5385 and BS 8000 Codes of Practice for the installation of wall and floor tiles.

For advice on tiling to different substrates refer to the Nicobond Tiling Products the directory brochure.

Health & Safety Advice

PRECAUTIONS

Always wear gloves and eye/face protection as necessary. Observe personal hygiene, particularly washing the hands after work has been completed or at any interruption whilst work is in progress. In case of accidents seek medical advice. Keep away from children.

The relevant Material Safety Data Sheet can be obtained from www.ncnicobond.com or directly from N & C Building Products Ltd at the address below.

The specification shall be Nicobond Starlike evo Special fx as manufactured by N&C Building Products Limited, 41-51 Freshwater Road, Chadwell Heath, Romford, Essex, RM8 1SP, England. Tel: 020 8586 4600 and shall be applied strictly in accordance with the Manufacturer's current data sheets and instructions.