

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : NICOBOND QUICKFIX ADHESIVE GREY C1 FT
Product code : N1161150

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : A cement based, fast setting thick or thin bed tile adhesive, suitable for fixing ceramic wall, terracotta and quarry tiles to sand/cement rendering, brick, blockwork, screed and concrete.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

N&C Building Products Limited
41/51 Freshwater Road
Chadwell Heath
RM8 1SP Romford - United Kingdom
T 0208 586 4600 - F 0208 586 4646
ncnicobond.com

1.4. Emergency telephone number

Emergency number : 0208 586 4600
OFFICE HOURS 08:00 - 17:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Specific target organ toxicity — Single exposure, Category 3, H335
Respiratory tract irritation
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

Signal word (CLP)

: Danger

Hazardous ingredients

: Portland Cement Klinker; Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide

Hazard statements (CLP)

: H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H412 - Harmful to aquatic life with long lasting effects.

NICOBOND QUICKFIX ADHESIVE GREY C1 FT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)

: P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER, a doctor.
P312 - Call a POISON CENTER, a doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
QUARTZ substance with a Community workplace exposure limit	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	50 - 75	Not classified
Portland Cement Klinker	(CAS-No.) 65997-15-1 (EC-No.) 266-043-4	1 - 30	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335
Calcium sulfate	(CAS-No.) 7778-18-9 (EC-No.) 231-900-3	1 - 5	Acute Tox. 4 (Oral), H302 STOT RE 2, H373 Aquatic Chronic 3, H412
Calcium Sulfoaluminate	(CAS-No.) 12004-14-7 (EC-No.) 234-448-5	1 - 5	STOT RE 2, H373 Aquatic Chronic 2, H411
Calcium aluminate aggregate, calcium aluminate flux		1 - 5	Aquatic Chronic 2, H411
Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide	(CAS-No.) 1305-62-0 (EC-No.) 215-137-3	< 1	Skin Corr. 1, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

NICOBOND QUICKFIX ADHESIVE GREY C1 FT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing dust, fume, gas, mist, spray, vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing dust, fume, gas, mist, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

QUARTZ (14808-60-7)

EU - Occupational Exposure Limits

Local name	Silica crystalline (Quartz)
------------	-----------------------------

IOELV TWA (mg/m ³)	0.05 mg/m ³ (respirable dust)
--------------------------------	--

Notes	(Year of adoption 2003)
-------	-------------------------

Regulatory reference	SCOEL Recommendations
----------------------	-----------------------

United Kingdom - Occupational Exposure Limits

Local name	Silica
------------	--------

WEL TWA (mg/m ³)	0.1 mg/m ³ respirable crystalline
------------------------------	--

Regulatory reference	EH40/2005 (Third edition, 2018). HSE
----------------------	--------------------------------------

Portland Cement Klinker (65997-15-1)

United Kingdom - Occupational Exposure Limits

Local name	Portland cement
------------	-----------------

WEL TWA (mg/m ³)	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
------------------------------	--

Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
----------------------	---------------------------------------

Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)

EU - Occupational Exposure Limits

Local name	Calcium dihydroxide
------------	---------------------

IOELV TWA (mg/m ³)	1 mg/m ³ (Respirable fraction)
--------------------------------	---

NICOBOND QUICKFIX ADHESIVE GREY C1 FT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

IOELV STEL (mg/m ³)	4 mg/m ³ (Respirable fraction)
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
United Kingdom - Occupational Exposure Limits	
Local name	Calcium hydroxide
WEL TWA (mg/m ³)	5 mg/m ³ 1 mg/m ³ Respirable fraction
WEL STEL (mg/m ³)	4 mg/m ³ Respirable fraction
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

In case of dust production: protective goggles. Gloves. Dust formation: dust mask.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: granules.
Colour	: Grey.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available

NICOBOND QUICKFIX ADHESIVE GREY C1 FT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Calcium Sulfoaluminate (12004-14-7)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 3.26 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Calcium sulfate (7778-18-9)

LD50 oral rat	> 1581 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LC50 Inhalation - Rat	> 3.26 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Calcium aluminate aggregate, calcium aluminate flux

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method)
LC50 Inhalation - Rat	> 2.3 mg/l air Animal: rat, Guideline: other:EPA 40 CFR 158 Guideline Reference #81-3, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Calcium Sulfoaluminate (12004-14-7)

NOAEL (chronic, oral, animal/male, 2 years)	256 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	284 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)

NICOBOND QUICKFIX ADHESIVE GREY C1 FT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Calcium sulfate (7778-18-9)	
NOAEL (chronic, oral, animal/male, 2 years)	256 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	284 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)

Reproductive toxicity : Not classified

Calcium aluminate aggregate, calcium aluminate flux	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (animal/female, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified

Calcium Sulfoaluminate (12004-14-7)	
LOAEL (oral, rat, 90 days)	237 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	79 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Calcium sulfate (7778-18-9)	
LOAEL (oral, rat, 90 days)	237 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	79 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Calcium aluminate aggregate, calcium aluminate flux	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.05 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Calcium Sulfoaluminate (12004-14-7)	
LC50 fish 1	> 83 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 Daphnia 1	6.8 mg/l Test organisms (species): Daphnia magna
EC50 Daphnia 2	7.7 mg/l Test organisms (species): Daphnia magna
EC50 72h algae (1)	47.4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h algae (2)	4.8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

NICOBOND QUICKFIX ADHESIVE GREY C1 FT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Calcium sulfate (7778-18-9)	
LC50 fish 1	> 79 mg/l Test organisms (species): Oryzias latipes
EC50 72h algae (1)	> 79 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Calcium aluminate aggregate, calcium aluminate flux	
EC50 72h algae (1)	4.5 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h algae (2)	> 5.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)	
NOEC chronic fish	50.6 mg/l

12.2. Persistence and degradability

Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)	
Persistence and degradability	Not relevant to classification of this product.

12.3. Bioaccumulative potential

Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)	
Bioaccumulative potential	Not relevant to classification of this product.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)	vPvB: not relevant – no registration required

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

NICOBOND QUICKFIX ADHESIVE GREY C1 FT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.