

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

|                               |                                                 |
|-------------------------------|-------------------------------------------------|
| Product form                  | : Mixture                                       |
| Product name                  | : NICOBOND RAPID TILE & STONE ADHESIVE GREY C2F |
| Product code                  | : N1161250                                      |
| Other means of identification | : UFI: 1T40-P0AR-100A-3RX3                      |

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

|                              |                                                                                                                                                                         |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use of the substance/mixture | : Cement based, single part, semi pourable rapid setting adhesive for fixing marble, limestone, granite, slate and natural stone tiles in interior or exterior settings |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

N&C Building Products Limited  
41/51 Freshwater Road  
Chadwell Heath  
RM8 1SP Romford - United Kingdom  
T 0208 586 4600 - F 0208 586 4646  
[ncnicobond.com](http://ncnicobond.com)

#### 1.4. Emergency telephone number

|                  |                                               |
|------------------|-----------------------------------------------|
| Emergency number | : 0208 586 4600<br>OFFICE HOURS 08:00 - 17:00 |
|------------------|-----------------------------------------------|

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

|                                                                                               |      |
|-----------------------------------------------------------------------------------------------|------|
| Skin corrosion/irritation, Category 2                                                         | H315 |
| Serious eye damage/eye irritation, Category 1                                                 | H318 |
| Skin sensitisation, Category 1                                                                | H317 |
| Specific target organ toxicity — Single exposure, Category 3,<br>Respiratory tract irritation | H335 |
| Hazardous to the aquatic environment — Chronic Hazard, Category 3                             | H412 |
| Full text of H statements : see section 16                                                    |      |


##### Adverse physicochemical, human health and environmental effects

May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05

GHS07

Signal word (CLP)

: Danger

Hazardous ingredients

: Portland Cement Klinker; formaldehyde ...%; Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide

Hazard statements (CLP)

: H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H335 - May cause respiratory irritation.  
H412 - Harmful to aquatic life with long lasting effects.

# NICOBOND RAPID TILE & STONE ADHESIVE GREY C2F

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Precautionary statements (CLP)

: P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection.  
P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER, a doctor.  
P312 - Call a POISON CENTER, a doctor if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name                                                                   | Product identifier                         | %       | Classification according to Regulation (EC) No. 1272/2008 [CLP]                      |
|------------------------------------------------------------------------|--------------------------------------------|---------|--------------------------------------------------------------------------------------|
| QUARTZ<br>substance with a Community workplace exposure limit          | (CAS-No.) 14808-60-7<br>(EC-No.) 238-878-4 | 50 - 75 | Not classified                                                                       |
| Portland Cement Klinker                                                | (CAS-No.) 65997-15-1<br>(EC-No.) 266-043-4 | 1 - 30  | Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1B, H317<br>STOT SE 3, H335    |
| Calcium sulfate                                                        | (CAS-No.) 7778-18-9<br>(EC-No.) 231-900-3  | 1 - 5   | Acute Tox. 4 (Oral), H302<br>STOT RE 2, H373<br>Aquatic Chronic 3, H412              |
| Calcium Sulfoaluminate                                                 | (CAS-No.) 12004-14-7<br>(EC-No.) 234-448-5 | 1 - 5   | STOT RE 2, H373<br>Aquatic Chronic 2, H411                                           |
| Calcium aluminate aggregate, calcium aluminate flux                    |                                            | 1 - 5   | Aquatic Chronic 2, H411                                                              |
| Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide | (CAS-No.) 1305-62-0<br>(EC-No.) 215-137-3  | < 1     | Skin Corr. 1, H314<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>Aquatic Chronic 1, H410 |

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Serious damage to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

# NICOBOND RAPID TILE & STONE ADHESIVE GREY C2F

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing dust, fume, gas, mist, spray, vapours. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### QUARTZ (14808-60-7)

##### EU - Occupational Exposure Limits

|                                |                                          |
|--------------------------------|------------------------------------------|
| Local name                     | Silica crystalline (Quartz)              |
| IOELV TWA (mg/m <sup>3</sup> ) | 0.05 mg/m <sup>3</sup> (respirable dust) |
| Notes                          | (Year of adoption 2003)                  |
| Regulatory reference           | SCOEL Recommendations                    |

#### Portland Cement Klinker (65997-15-1)

##### United Kingdom - Occupational Exposure Limits

|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| Local name                   | Portland cement                                                            |
| WEL TWA (mg/m <sup>3</sup> ) | 10 mg/m <sup>3</sup> inhalable dust<br>4 mg/m <sup>3</sup> respirable dust |
| Regulatory reference         | EH40/2005 (Fourth edition, 2020). HSE                                      |

#### Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)

##### EU - Occupational Exposure Limits

|                                 |                                           |
|---------------------------------|-------------------------------------------|
| Local name                      | Calcium dihydroxide                       |
| IOELV TWA (mg/m <sup>3</sup> )  | 1 mg/m <sup>3</sup> (Respirable fraction) |
| IOELV STEL (mg/m <sup>3</sup> ) | 4 mg/m <sup>3</sup> (Respirable fraction) |
| Regulatory reference            | COMMISSION DIRECTIVE (EU) 2017/164        |

##### United Kingdom - Occupational Exposure Limits

|            |                   |
|------------|-------------------|
| Local name | Calcium hydroxide |
|------------|-------------------|

# NICOBOND RAPID TILE & STONE ADHESIVE GREY C2F

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

|                      |                                        |
|----------------------|----------------------------------------|
| WEL TWA (mg/m³)      | 5 mg/m³<br>1 mg/m³ Respirable fraction |
| WEL STEL (mg/m³)     | 4 mg/m³ Respirable fraction            |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE  |

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protective equipment:

In case of dust production: protective goggles. Gloves. Dust formation: dust mask.

|                                                                          |
|--------------------------------------------------------------------------|
| <b>Hand protection:</b>                                                  |
| Protective gloves                                                        |
| <b>Eye protection:</b>                                                   |
| Safety glasses                                                           |
| <b>Skin and body protection:</b>                                         |
| Wear suitable protective clothing                                        |
| <b>Respiratory protection:</b>                                           |
| In case of insufficient ventilation, wear suitable respiratory equipment |

#### Personal protective equipment symbol(s):



#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                            |                     |
|--------------------------------------------|---------------------|
| Physical state                             | : Solid             |
| Appearance                                 | : granules.         |
| Colour                                     | : Grey.             |
| Odour                                      | : odourless.        |
| Odour threshold                            | : No data available |
| pH                                         | : No data available |
| pH solution                                | : 12 - 13           |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point                              | : No data available |
| Freezing point                             | : Not applicable    |
| Boiling point                              | : No data available |
| Flash point                                | : Not applicable    |
| Auto-ignition temperature                  | : Not applicable    |
| Decomposition temperature                  | : No data available |
| Flammability (solid, gas)                  | : Non flammable.    |
| Vapour pressure                            | : No data available |
| Relative vapour density at 20 °C           | : No data available |
| Relative density                           | : No data available |
| Solubility                                 | : No data available |
| Log Pow                                    | : No data available |
| Viscosity, kinematic                       | : No data available |
| Viscosity, dynamic                         | : No data available |
| Explosive properties                       | : No data available |
| Oxidising properties                       | : No data available |
| Explosive limits                           | : Not applicable    |

# NICOBOND RAPID TILE & STONE ADHESIVE GREY C2F

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

| Calcium Sulfoaluminate (12004-14-7) |                                                                                                                                         |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat                       | > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method) |
| LD50 dermal rat                     | > 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.3 (Acute Toxicity (Dermal))                               |
| LC50 Inhalation - Rat               | > 3.26 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)                                                  |

| Calcium sulfate (7778-18-9) |                                                                                                                                  |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat               | > 1581 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method) |
| LC50 Inhalation - Rat       | > 3.26 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)                                           |

| Calcium aluminate aggregate, calcium aluminate flux |                                                                                                                                                                                                                         |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LD50 oral rat                                       | > 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method) |
| LC50 Inhalation - Rat                               | > 2.3 mg/l air Animal: rat, Guideline: other:EPA 40 CFR 158 Guideline Reference #81-3, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)                                                                        |

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye damage.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

| Calcium Sulfoaluminate (12004-14-7)           |                                                                                                                                                               |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (chronic, oral, animal/male, 2 years)   | 256 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)   |
| NOAEL (chronic, oral, animal/female, 2 years) | 284 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information) |

| Calcium sulfate (7778-18-9)                   |                                                                                                                                                               |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (chronic, oral, animal/male, 2 years)   | 256 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)   |
| NOAEL (chronic, oral, animal/female, 2 years) | 284 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information) |

# NICOBOND RAPID TILE & STONE ADHESIVE GREY C2F

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reproductive toxicity : Not classified

### Calcium aluminate aggregate, calcium aluminate flux

|                             |                                                                                                                                                                                            |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NOAEL (animal/male, F0/P)   | 1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)   |
| NOAEL (animal/female, F0/P) | 1000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified

### Calcium Sulfoaluminate (12004-14-7)

|                            |                                                                                                                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOAEL (oral, rat, 90 days) | 237 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| NOAEL (oral, rat, 90 days) | 79 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)  |

### Calcium sulfate (7778-18-9)

|                            |                                                                                                                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOAEL (oral, rat, 90 days) | 237 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| NOAEL (oral, rat, 90 days) | 79 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)  |

### Calcium aluminate aggregate, calcium aluminate flux

|                                                 |                                                                                                         |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| LOAEC (inhalation, rat,dust/mist/fume, 90 days) | 0.05 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------|

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

### Calcium Sulfoaluminate (12004-14-7)

|                    |                                                                                                      |
|--------------------|------------------------------------------------------------------------------------------------------|
| LC50 fish 1        | > 83 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)                   |
| EC50 Daphnia 1     | 6.8 mg/l Test organisms (species): Daphnia magna                                                     |
| EC50 Daphnia 2     | 7.7 mg/l Test organisms (species): Daphnia magna                                                     |
| EC50 72h algae (1) | 47.4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| EC50 72h algae (2) | 4.8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)  |

### Calcium sulfate (7778-18-9)

|                    |                                                                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| LC50 fish 1        | > 79 mg/l Test organisms (species): Oryzias latipes                                                                                       |
| EC50 72h algae (1) | > 79 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |

# NICOBOND RAPID TILE & STONE ADHESIVE GREY C2F

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| Calcium aluminate aggregate, calcium aluminate flux |                                                                                                                                            |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| EC50 72h algae (1)                                  | 4.5 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)   |
| EC50 72h algae (2)                                  | > 5.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |

| Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0) |           |
|------------------------------------------------------------------------------------|-----------|
| NOEC chronic fish                                                                  | 50.6 mg/l |

### 12.2. Persistence and degradability

| Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0) |                                                 |
|------------------------------------------------------------------------------------|-------------------------------------------------|
| Persistence and degradability                                                      | Not relevant to classification of this product. |

### 12.3. Bioaccumulative potential

| Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0) |                                                 |
|------------------------------------------------------------------------------------|-------------------------------------------------|
| Bioaccumulative potential                                                          | Not relevant to classification of this product. |

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

| Component                                                                          |                                               |
|------------------------------------------------------------------------------------|-----------------------------------------------|
| Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0) | vPvB: not relevant – no registration required |

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

| ADR                                    | IMDG          | IATA          | ADN           | RID           |
|----------------------------------------|---------------|---------------|---------------|---------------|
| 14.1. UN number                        |               |               |               |               |
| Not regulated                          | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.2. UN proper shipping name          |               |               |               |               |
| Not regulated                          | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.3. Transport hazard class(es)       |               |               |               |               |
| Not regulated                          | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.4. Packing group                    |               |               |               |               |
| Not regulated                          | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.5. Environmental hazards            |               |               |               |               |
| Not regulated                          | Not regulated | Not regulated | Not regulated | Not regulated |
| No supplementary information available |               |               |               |               |

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

#### Inland waterway transport

Not regulated

# NICOBOND RAPID TILE & STONE ADHESIVE GREY C2F

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Rail transport

Not regulated

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

| Full text of H- and EUH-statements: |                                                                                            |
|-------------------------------------|--------------------------------------------------------------------------------------------|
| Acute Tox. 4 (Oral)                 | Acute toxicity (oral), Category 4                                                          |
| Aquatic Chronic 1                   | Hazardous to the aquatic environment — Chronic Hazard, Category 1                          |
| Aquatic Chronic 2                   | Hazardous to the aquatic environment — Chronic Hazard, Category 2                          |
| Aquatic Chronic 3                   | Hazardous to the aquatic environment — Chronic Hazard, Category 3                          |
| Eye Dam. 1                          | Serious eye damage/eye irritation, Category 1                                              |
| Skin Corr. 1                        | Skin corrosion/irritation, Category 1                                                      |
| Skin Irrit. 2                       | Skin corrosion/irritation, Category 2                                                      |
| Skin Sens. 1B                       | Skin sensitisation, category 1B                                                            |
| STOT RE 2                           | Specific target organ toxicity — Repeated exposure, Category 2                             |
| STOT SE 3                           | Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation |
| H302                                | Harmful if swallowed.                                                                      |
| H314                                | Causes severe skin burns and eye damage.                                                   |
| H315                                | Causes skin irritation.                                                                    |
| H317                                | May cause an allergic skin reaction.                                                       |
| H318                                | Causes serious eye damage.                                                                 |
| H335                                | May cause respiratory irritation.                                                          |
| H373                                | May cause damage to organs through prolonged or repeated exposure.                         |
| H410                                | Very toxic to aquatic life with long lasting effects.                                      |
| H411                                | Toxic to aquatic life with long lasting effects.                                           |
| H412                                | Harmful to aquatic life with long lasting effects.                                         |

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*