

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Product name	: NICOBOND STANDARD SET FLEX ADHESIVE GREY C2 TE
Product code	: N1193050
Other means of identification	: UFI: P120-G081-700F-X6M4

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture	: Standard setting, enhanced, cement based adhesive for fixing ceramic wall & floor tiles, porcelain, mosaic and natural stones in interior & exterior situations
------------------------------	---

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

N&C Building Products Limited  
41/51 Freshwater Road  
Chadwell Heath  
RM8 1SP Romford - United Kingdom  
T 0208 586 4600 - F 0208 586 4646  
[ncnicobond.com](http://ncnicobond.com)

#### 1.4. Emergency telephone number

Emergency number	: 0208 586 4600 OFFICE HOURS 08:00 - 17:00
------------------	---

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: Portland Cement Klinker; Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide

Hazard statements (CLP)

: H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H335 - May cause respiratory irritation.

# NICOBOND STANDARD SET FLEX ADHESIVE GREY C2 TE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP) : P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection.  
P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER, a doctor.  
P312 - Call a POISON CENTER, a doctor if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
QUARTZ substance with a Community workplace exposure limit	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	50 - 75	Not classified
Portland Cement Klinker	(CAS-No.) 65997-15-1 (EC-No.) 266-043-4	1 - 50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335
Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide	(CAS-No.) 1305-62-0 (EC-No.) 215-137-3	< 1	Skin Corr. 1, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Serious damage to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

# NICOBOND STANDARD SET FLEX ADHESIVE GREY C2 TE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing dust. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

QUARTZ (14808-60-7)	
<b>EU - Occupational Exposure Limits</b>	
Local name	Silica crystalline (Quartz)
IOELV TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable dust)
Notes	(Year of adoption 2003)
Regulatory reference	SCOEL Recommendations
<b>Portland Cement Klinker (65997-15-1)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Portland cement
WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> inhalable dust 4 mg/m <sup>3</sup> respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)</b>	
<b>EU - Occupational Exposure Limits</b>	
Local name	Calcium dihydroxide
IOELV TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (Respirable fraction)
IOELV STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup> (Respirable fraction)
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Calcium hydroxide
WEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> 1 mg/m <sup>3</sup> Respirable fraction
WEL STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup> Respirable fraction
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protective equipment:

In case of dust production: protective goggles. Gloves. Dust formation: dust mask.

# NICOBOND STANDARD SET FLEX ADHESIVE GREY C2 TE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

### Personal protective equipment symbol(s):



### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: granules.
Colour	: Grey.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
pH solution	: 12 - 13
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

# NICOBOND STANDARD SET FLEX ADHESIVE GREY C2 TE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

### Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)

NOEC chronic fish	50.6 mg/l
-------------------	-----------

### 12.2. Persistence and degradability

### Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)

Persistence and degradability	Not relevant to classification of this product.
-------------------------------	---

### 12.3. Bioaccumulative potential

### Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)

Bioaccumulative potential	Not relevant to classification of this product.
---------------------------	---

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### Component

Hydrated Lime, Calcium dihydroxide, Calcium Hydrate, Calcium hydroxide (1305-62-0)	vPvB: not relevant – no registration required
--	---

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

# NICOBOND STANDARD SET FLEX ADHESIVE GREY C2 TE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				
14.6. Special precautions for user				
<b>Overland transport</b>				
Not regulated				
<b>Transport by sea</b>				
Not regulated				
<b>Air transport</b>				
Not regulated				
<b>Inland waterway transport</b>				
Not regulated				
<b>Rail transport</b>				
Not regulated				
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code				
Not applicable				

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

# NICOBOND STANDARD SET FLEX ADHESIVE GREY C2 TE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*