



UNICLASS	EPIC
CI/SfB	Y

Technical data sheet

May 2024

# Primer

## Description

Nicobond Primer – An acrylic dispersion specially formulated to improve adhesion and inhibiting penetration of water in intermittently damp locations. Nicobond primer is used as a pore sealer on floor surfaces to prevent air bubbles rising through subsequently applied sub-floor smoothing compounds and to prolong their flow life and workability. Ideal for priming cement: sand renders, screeds and concrete surfaces prior to the application of Nicobond ceramic tile adhesives.

**Always refer to the latest Technical Data Sheet for the individual Nicobond product Nicobond Primer is to be used with prior to use.**

## Application

Shake container well before use. Dilute if required. Apply the primer evenly, using a brush or broom, over the sound, clean and dust-free surface and leave to dry to a clear thin film. Do not allow to pool.

### System 1 – Slurry Priming

A most effective primer for all cement-based adhesives and screeds, internally and externally, is to brush tightly onto the surface a thin even layer of a well stirred mixture of:- 1 volume water 1 volume Nicobond Primer 1 volume of Nicobond cement-based product that will then be used. The layer should normally be allowed to set for a few hours before work progresses. **Coverage:** Approximately 6m<sup>2</sup> per litre of Nicobond Primer.

### System 2 – Priming/Sealing exterior

For the simple priming/sealing of all cementitious and other surfaces particularly for exterior work, brush into the surface a thin even layer of a blend of:- 4 volumes water 1 volume Nicobond Primer mixed by thorough stirring. Allow layer to dry slightly before applying Nicobond smoothing compounds or adhesives. **Coverage:** Approximately 30m<sup>2</sup> per litre of Nicobond Primer.

### System 3 – Priming/Sealing interior

For the simple priming/sealing of most interior surfaces brush apply a thin even layer of a blend of:- 4 volumes water : 1 volume Nicobond Primer mixed by thorough stirring. Allow layer to thoroughly dry before continuing. **Coverage:** Approximately 30m<sup>2</sup> per litre of Nicobond Primer.

### System 4 – Non-Absorbent Surfaces

A most effective primer for all cement-based screeds, brush into the surface a thin even layer of undiluted/heat Nicobond Primer. Allow to dry for a few hours before work progresses. **Coverage:** Approximately 6 – 10m<sup>2</sup> per litre of Nicobond Primer, depending on surface porosity.

### System 5 – Anhydrite Screeds

Prime with 2 coats Nicobond Primer applied at right angles to each other diluted 1: 3 with water.



internal



external

water  
resistantswimming  
poolsLifetime  
guarantee

Application Data	
Size :	5 Litres & 1 Litre
Packaging	Polyethylene containers Protect from frost and direct sunlight.
Walk on time @ 20° C	Approx 20 minutes.
Installation Temperature	Minimum 5° C
Shelf Life	A minimum of 12 months in the original unopened containers.


## Features

Interior and exterior use  
Water-based and non-flammable.  
Dries almost transparent, will not stain  
Reduces porosity of surfaces.

## Health & Safety Advice

Nicobond Primer is Non-Irritant, but irritation may occur if dried material adheres to the skin, avoid contact with skin, eyes and clothing. Do not swallow. Wear suitable protective clothing, chemical resistant gloves and eye/face protection. Keep away from children.

The relevant Material Safety Data Sheet can be obtained from [www.ncnicobond.com](http://www.ncnicobond.com) or directly from N & C Building Products Ltd at the address below.



#### Distribution Centres, Trade Counters & Showrooms

N&C Building Materials  
41 - 51 Freshwater Road  
Chadwell Heath,  
Romford Essex RM8 1SP  
Tel: 020 8586 4600  
Fax: 020 8586 4646

C1 Cothill Trading Estate  
Plympton  
Plymouth PL7 1SR  
Tel: 01752 339724  
Fax: 01752 342746

B1 - B3 Sneyd Trading Estate  
Sneyd Hill, Burslem  
Stoke on Trent ST6 2PA  
Tel: 01782 575727  
Fax: 01782 575641

26 Colquhoun Avenue  
Hillington  
Glasgow G52 4BN  
Tel: 0141 880 1200  
Fax: 0141 880 1212

4 Waterloo Industrial Estate  
Flanders Road  
Hedge End  
Southampton SO30 2QT  
Tel: 01489 779700  
Fax: 01489 779701

3 - 4 Cardiff Trade Park  
Hadfield Road  
Cardiff CF11 8AQ  
Tel: 02920 390146  
Fax: 02920 224356

2 City Park Industrial Estate  
Gelder Road  
Leeds LS12 6DR  
Tel: 0113 224 4630  
Fax: 0113 224 4631

#### Trade Counters & Showrooms

1A - 1B Alexander Place  
Lower Park Road  
New Southgate  
London N11 1QD  
Tel: 020 8361 6050  
Fax: 020 8361 4757

14 Meridian Trading Estate  
Bugsby Way, Charlton  
London SE7 7SJ  
Tel: 020 8269 5960  
Fax: 020 8269 5961

Units 10 - 11, 14 - 15  
Advent Way, Edmonton  
London N18 3AF  
Tel: 020 8586 4600  
Fax: 020 8586 4646

8 Ascent Park  
Edinburgh Way,  
Harlow Essex CM20 2HW  
Tel: 01279 621980  
Fax: 01279 621981

16 Arlington Business Park  
Whittle Way, Stevenage  
Hertfordshire SG1 2BD  
Tel: 01206 849 322  
Fax: 01438 740 338

8D Pompey Centre, Fratton Way  
Southsea, Portsmouth PO4 8TA  
Tel: 02392 894599  
Fax: 02392 894598

5 Tower Court, St David's Road  
Swansea Enterprise Park  
Swansea SA6 8RU  
Tel: 01792 797337  
Fax: 01792 774019