


Starlike evo Gel Stripper

- Cleaner gel for the removal of epoxy grout residue
 - Also effective for the deep cleaning of tough dirt
 - Clear gel made from a mix of solvents
 - Apply with a trowel or brush on both horizontal and vertical surfaces.
 - Thick and viscous consistency makes it easy to apply even on walls
 - Effective in removing cured & consolidated epoxy residue
- Ready to use
 - Starlike evo Gel Stripper is designed for the total removal of Starlike evo Extreme Performance Grout set epoxy grouts in joints
 - Effective on halos left on ceramic surfaces due to incorrect or insufficient cleaning
 - 10-20 minutes are normally sufficient for halos and 1 to 8 hours for the removal of set grout

Application Data	
COLOUR	Colourless Clear Gel
MIXING RATIO	Ready to use
MIXING	Shake well before use. The product is ready to use and does not require any dilution. Spread a thin, even layer of product on the parts to be removed using a brush or trowel. Let the Starlike evo Gel Stripper work until the residue has softened.
CONSISTENCY OF MIX	Viscous gel
COVERAGE	3 - 10 m ² /l
TREATMENT	10 to 20 minutes up to 8 hours
FLAMMABLE	Yes
APPLICATION	Smooth steel trowel or brush
APPLICATION TEMPERATURE	From +5°C to +35°C
OPERATING TEMPERATURE	From -5°C to +80°C
PACKAGING	750ml metal container
SHELF LIFE	24 months in original packaging away from sources of heat and direct sunlight



Starlike evo Gel Stripper

BRITISH STANDARDS AND GUIDELINES:

All aspects of any installation of the Nicobond range of products must be carried out in compliance with the directives of the relevant British Standard requirements of BS5385 codes of practice for wall and floor tiling. With reference to and The Tile Association guidelines. All installations must be carried out in strict accordance with the manufacturer's instructions featured in the relevant Technical Data Sheets (TDS).

DESCRIPTION:

Nicobond Starlike Evo Gel Stripper is designed for the complete removal of Nicobond Starlike evo Extreme Performance Grout set epoxy grouts in joints, or halos left on ceramic surfaces due to incorrect or insufficient cleaning.

APPLICATION:

Spread the product at temperatures between +5°C and +35°C. Do not dilute further with water or solvents. Before use, protect doors, windows, rubber gaskets, furniture, taps and fittings, metal or PVC profiles and any surfaces that may be damaged by direct contact with the product. Soak up any spills immediately using an absorbent material (paper, sawdust, etc.) and dispose the waste in a suitable container. Do not use on non-solvent-resistant products such as plastics, PVC, linoleum, decorative enamels, etc. If using with polished or honed tiles and polished natural stones, perform a spot test first in an inconspicuous area to confirm that the product doesn't dull the surface. Only use for applications as listed above.

Handle the product with extreme care as it is flammable. Do not smoke during use.

1. Shake well before use.
2. The product is ready to use and does not require any dilution.
3. Spread a thin, even layer of product on the parts to be removed using a brush or trowel.
4. Let the Nicobond Starlike Evo Gel Stripper work until the residue has softened.
5. Allowing the product to dwell for 10 to 20 minutes is normally sufficient for halos and 1 to 8 hours for the removal of cured grout.

6. Remove any residual epoxy grout with the aid of a metal trowel taking care not to damage the face of the tiles.
7. Wipe with a clean, dry cloth to remove the gel and rinse with plenty of clean water. Change the rinse water frequently.
8. If necessary, proceed with a second wash.

CLEANING:

Clean tools immediately after application.

See Nicobond "Tiling Products: The Directory" for full details of our extensive range of tiling and flooring products and tiling solutions. Refer to the latest version of our Technical Data Sheets and Safety Data Sheets to ensure compatibility before use, these can be downloaded from our website www.ncnicobond.com

MANUFACTURERS WARRANTY:

Nicobond products are covered by our lifetime warranty. Whilst we strive to ensure that any advice, recommendations, or information provided in our literature are accurate and up to date, we have no control over the conditions under which our products are used. It is therefore the responsibility of the end user to ensure that the product and its application are suitable for the intended purpose. No warranty is given, nor liability accepted, beyond the assurance that the product supplied will conform to our written specifications. End users must consult the latest version of the Technical Data Sheet and Safety Data Sheet prior to use, both of which are available from our website or upon request. We do not accept any liability for workmanship or any consequential loss or damage.



High performance products tiling & flooring professionals

The information contained on this data sheet is given in good faith. It is to the best of our knowledge true and accurate; however, it may contain information which is inappropriate under certain conditions of use. The company cannot accept responsibility for any loss or damage due to inappropriate use or the possibility of variations of working conditions and of workmanship outside our control.

N & C Building Products Limited
41-51 Freshwater Road, Chadwell Heath
Romford Essex RM8 1SP
Tel: 020 8586 4600
Email: info@nichollsandclarke.com
Web: www.nichollsandclarke.com

Starlike evo Gel Stripper

HEALTH AND SAFETY:

2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02



GHS05



GHS07

Signal word Danger

· Hazard-determining components of labelling:

1,3-dioxolane, acetone, toluene

· Hazard statements

H225 Highly flammable liquid and vapour.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

UFI: HX90-10RJ-E00G-T0TP



High performance products tiling & flooring professionals

The information contained on this data sheet is given in good faith. It is to the best of our knowledge true and accurate; however, it may contain information which is inappropriate under certain conditions of use. The company cannot accept responsibility for any loss or damage due to inappropriate use or the possibility of variations of working conditions and of workmanship outside our control.

N & C Building Products Limited
41-51 Freshwater Road, Chadwell Heath
Romford Essex RM8 1SP
Tel: 020 8586 4600
Email: info@nichollsandclarke.com
Web: www.nichollsandclarke.com